

NERI

Large Projector Light
Source: LED
Mounting: Surface Mounted

Technical sheet
Measures in mm

DESCRIPTION

Compliance

EN 60598-1

BIS



Mechanical Information

Height	Length	Depth	IP	IK
215mm	647mm	140mm	66	08

Electrical characteristics

Voltage	Frequency	Cos φ	Insulation class	Operative Temp.
AC230V	50Hz	> 0.9	CL I	-35°C to -50°C

Fixing

- Suitable for surface mounting installation.

Materials

- Die-cast aluminium.
- Tempered glass.
- Silicon.
- Stainless steel.

Structure - Main components

- Body in rectangular shape made of high pressure die cast aluminium .
- Screen made of clear tempered Glass.
- Silicon gasket between frames ensures the ingress protection.
- Stainless steel screws for fixing.

Electrical auxiliaries


- Cable entry through cable gland.
- One cable of 3Cx1.5 sq.mm. supplied.
- Driver-standard on-off inbuilt power supply.

Operations and maintenance


- A scheduled maintenance program must be carried out on the Installation.
- Disconnect the electrical supply before maintenance operation.

Finish

- Standard color-Grey
- Powder coated for high corrosion resistance.



Front View



Side View

DESCRIPTION

Optics

Lighting distribution	Glass
10°/15°/25°/30°/45°/60°	Clear

- Lens made of PC.

Luminous flux

3000K			System
Code	lm	W	lm/W
NFL-5-270	21600	270	80

Luminous flux

4000K			System
Code	lm	W	lm/W
NFL-5-270	22950	270	85

- The energetic values in the table are referred to the system.
- LED source - SMD
- Heat sink integrated in the body.
- Lifetime (EN 62722-2-1, LM80 data): L70 > 50,000hours.
- Colour Rendering Index: Ra > 80.

Driver

- Standard on-off inbuilt power supply.

Accessories (Not included in standard product, to be ordered separately)



IP 68 3 Way connector for suitable cable diameter (6.5mm - 9.5mm)



IP 68 2 Way connector for suitable cable diameter (6.5mm - 9.5mm)

PHOTOMETRIC CURVES

Lighting distribution

